

QUIKGRIP[®]
METAL2WOOD

The Metal2Wood fastener is designed to attach steel roofing and siding used in post-frame and residential metal roofing applications.

The high hex washer head provides driving stability, its HiLo threads make for superior holding strength, and the Type 17 point allows for quick installation. The bonded seal washer creates a truly Weather-Tite seal – even when driven at an angle.



Type 17 point crills with a "point wetting," reducing metal shavings that can become embedded in the rubber washer.

The mechanical zinc plating provides extended corrosion resistance.

STANDARD



OPTIONAL



SIZE	HEAD	CARTON QTY	WEIGHT/M
"0 x 1"	1/4" HWH	2500	8.25
"0 x 1-1/2"	1/4" HWH	2500	10.321
"0 x 2"	1/4" HWH	2000	12.495
"0 x 2-1/2"	1/4" HWH	1500	15.068
"0 x 3"	1/4" HWH	1000	16.867
"2 x 3/4" STITCH	1/4" HWH	5000	10.587

WASHER SIZES	
ID	OD
.214"	.470"

QUIKGRIP[®]
METAL2WOOD HD
HD
HD

The Metal2Wood HD is your "rescue screw." It can replace nails or fasteners that have loosened and backed out of metal roofing and siding.

The EPDM rubber is vulcanized to the steel washer to prevent delaminating to form an excellent seal - even when driven at an angle. The 5/16" HWH with bonded sealing washer will cover the existing hole entirely, creating a watertight seal, even if stretched out by movement of the



metal roof. The mechanical zinc plating provides extended corrosion resistance.

STANDARD



OPTIONAL



SIZE	HEAD	CARTON QTY	WEIGHT/M
"4 x 1"	5/16" HWH	2500	8.25
"4 x 1-1/2"	5/16" HWH	2000	10.321
"4 x 2"	5/16" HWH	1500	12.495

WASHER SIZES	
ID	OD
.275"	.590"

POINT DIAMETER

25th TYPE 17 .191 / .202 .130 / .126 .246 / .251 2293 LBS. 60 IN.-LBS. 1890 LBS.

PULL OUT STRENGTH

SUBSTRATES							
PLYWOOD	OSB	SOUTHERN PINE		SPRUCE PINE FIR		OAK	HEMLOCK FIR
		1"	1-1/2"	1"	1-1/2"		
3/4	1/2	7/16	1"	1-1/2"	1"	1-1/2"	1"
709	584	313	710	1185	495	1043	1895

PULL OVER STRENGTH

DESIGNATION		MATERIAL	
AZ55 GALVALUME		AZ55 GALVALUME	
NOM. GAUGE	29		26
THICKNESS	.015		.019
#10 x .472	379		630
#10 x .500	422		655

POINT DIAMETER

30th TYPE 17 .245 / .248 .185 / .178 .312 / .305 4272 LBS. 125 IN.-LBS. 2995 LBS.

PULL OUT STRENGTH

SUBSTRATES							
PLYWOOD	OSB	SOUTHERN PINE		SPRUCE PINE FIR		OAK	HEMLOCK FIR
		1"	1-1/2"	1"	1-1/2"		
3/4	1/2	7/16	1"	1-1/2"	1"	1-1/2"	1"
845	646	296	1186	-	653	-	638

PULL OVER STRENGTH

DESIGNATION		MATERIAL	
AZ55 GALVALUME		AZ55 GALVALUME	
NOM. GAUGE	29	26	24
THICKNESS	.015	.019	.024
14mm x .551	483	781	1079
HWH	483	721	1042